

TECHNICAL SPECIFICATIONS FANTIC XXF 250

ENGINE:

Type: Single-cylinder 4-strokes, liquid cooled, 4 valves, DOHC

Displacement: 250 cc **Induction**: Fuel Injection

Bore: 77.0 mm Stroke: 53.6 mm

Compression ratio: 13.8: 1

Ignition system: TCI

Starting system: Electric starter **Lubrication system:** Wet sump

Trasmission: 5-speed **Clutch:** Wet, multiple-disc

CHASSIS:

Frame type: Aluminum perimeter frame

Caster angle: 26.5°

Trail: 119 mm

Rear frame: Aluminum

Swingarm: Aluminum with variable section and progressive link

Rims: 21x1.60 – 19x1.85

Tyres: 80/100x21 - 100/90x19

Brakes: Hydraulic disc ø270mm - Hydraulic disc ø240mm

 $\textbf{Front suspension} : \mathsf{KYB} \ \mathsf{\emptyset48} \ \mathsf{mm}, \ \mathsf{fully adjustable}, \ \mathsf{wheel travel 310} \ \mathsf{mm}$

Rear suspension: KYB, fully adjustable, wheel travel 317 mm

OVERALL DIMENSIONS:

Length: 2175 mm
Width: 825 mm
Height: 1285 mm
Seat height: 970 mm
Wheelbase: 1475 mm
Kerb weight: 102 kg
Fuel tank capacity: 6.2 I
Engine oil quantity: 0.95 I